



## 1320 DIGI-MET® Pocket calipers



1320 416



1320 517



### Specification

- Inductive measuring system, resistant to damp and sweat
- Stainless steel
- LCD display 11 mm without data output, 7.5 mm with data output
- DIN 862
- Locking screw
- Inside cross points
- Four way measurement with measuring ranges 150 and 200 mm
- Three way measurement with measuring range 300 mm

### Electronic functions

- ON/OFF switch
- QuickStart Electronic
- QuickLock Function
- Zero setting at any position
- mm/inch conversion
- Variable data output RS 232 + Digimatic + USB

### Shipment

- Plastic case, 1320 518 = Wooden case

		Measuring range		Jaw length		Reading		Depth gauge	Ref. No.	List price Euro
		mm	inch	mm	inch	mm	inch			
<b>Without data output</b>										
▪		150	6	40	1.57	0.01	.0005	Ø 1.5 mm	1320 416	105.00
▪		150	6	40	1.57	0.01	.0005	rectangular	1320 417	105.00
<b>With DATA VARIABLE</b>										
▪		150	6	40	1.57	0.01	.0005	Ø 1.5 mm	1320 516	137.00
▪		150	6	40	1.57	0.01	.0005	rectangular	1320 517	137.00
		200	8	50	1.97	0.01	.0005	rectangular	1320 519	172.00
		300	12	65	2.34	0.01	.0005	without	1320 522	221.00
<b>With DATA VARIABLE, with long inside cross points</b>										
		150	6	40	1.57	0.01	.0005	Ø 1.5 mm	1320 518	370.00

### Accessories

	Ref. No.	List price Euro
Battery, 3V-Lithium, CR 2032	0220 704	3.60
Cable for USB, incl. software	1998 720	66.00
Cable for RS 232	1997 501	46.20
Cable for Digimatic	1998 501	59.00